



## Downloadable Dynamometer Database (D<sup>3</sup>)- Test Summary Sheet

### 2012 Fiat 500

Vehicle Architecture	Conventional
Document Date	10/2/2012
Revision Number	1
Notes: 2 door Sport / 1.4L	

### Vehicle Setup Information

Test Cell Location	2WD
Vehicle Dynamometer Input	
Test weight [lb]	2750
Target A [lb]	30.31
Target B [lb/mph]	0.2259
Target C [lb/mph <sup>2</sup> ]	0.01776
Test Fuel Information	
Fuel type	Tier II EEE HF437
Fuel density [g/ml]	0.743
Fuel Net HV [BTU/lbm]	18344



Test ID [HF]	Cycle	Cold start (Cst) Hor start [HS]	Date	Test Cell Temp [C]	Test Cell RH [%]	Test Cell Baro [in/Hg]	Vehicle cooling fan speed: Speed Match [SM] or constant speed [CS]	Solar Lamps [W/m <sup>2</sup> ]	Vehicle Climate Control settings	Hood Position [Up] or [Closed]	Window Position [Closed] or [Down]	Cycle Distance [mi]	Cycle Fuel economy [mpg] [Fuel scale]	Cycle HV battery Integrated net current [DC Ah]	Cycle HV battery Average Zero crossing Voltage [V]	Cycle HV battery Net Energy [DC kWh]	Cycle HV battery Net Energy Consumption [DC Wh/mi]
Test information			Test cell information			Test cell setup		Vehicle setup				Electric energy consumption					
<b>Test sequence purpose: Standard testing</b>																	
71207085	UDDS CS	CSt	07/27/12	21.09	75.66	29.08	Cst spd	Off	Off	Up	Down	7.44	31.8				
71207086	UDDS HS	HSt	07/27/12	21.06	74.46	29.08	Cst spd	Off	Off	Up	Down	7.43	35.9				
71207076	Highway	HSt	07/26/12	21.30	74.23	28.95	Cst spd	Off	Off	Up	Down	10.24	47.8				
71207077	US06	HSt	07/26/12	21.36	72.62	28.96	Cst spd	Off	Off	Up	Down	3.99	32.1				
71207083	Steady State Speeds	HSt	07/26/12	21.34	67.82	28.99	Cst spd	Off	Off	Up	Down						
<b>Full charge test summary</b>												<b>Totals</b>	<b>29.10</b>				
<b>Re-charging information</b>			N/A Ambient temperature during charge						HV battery integrated current [DC Ah]		N/A						
Level:									Charger integrated current [AC Ah]		N/A						
									HV battery integrated power [DC kWh]		N/A						
									Charger integrated power [AC kWh]		N/A						

**Summary notes**  
 For the highway and US06 cycles only the second (hot) test results are presented in this summary.  
 Electric energy consumption:  
 HV battery Integrated net current --> Integrated current as reported by power analyzer  
 HV battery Average Zero crossing Voltage --> Calculated Average Zero crossing Voltage over the phase or cycle  
 HV Net Energy --> Integrated power as reported by power analyzer  
 Note that HV Net Energy is not equal to the product of HV battery Integrated net current times Average Zero crossing Voltage.  
 \* The vehicle coast down information for EPA

**Advanced Powertrain Research Facility Data referencing:**

- This data has originated from the Argonne National Laboratory D<sup>3</sup> website. [http://webapps.anl.gov/vehicle\\_data/](http://webapps.anl.gov/vehicle_data/)
- The purpose of this information is to provide advanced technology vehicle chassis dynamometer test data for the engineering community. Mostly comprised of vehicle benchmarking test results, it is intended for the better understanding of the technology and for education. Data from this website may not be used as a source for publication or profit without consent of Argonne National Laboratory.
- Please contact [d3info@anl.gov](mailto:d3info@anl.gov) for questions, comments or inquiries.